

# PHAROS NETWORK SWITCH



# FSW2422-24P



سوئیچ ۲۴ پورت PoE  
بهمراه ۴ پورت Uplink  
2 × SFP  
2 × GB

# FSW2422-24P



Ethernet Port	2*10/100/1000 Base-T 2*1000 Base-X 24*10/100 Base-T (PoE power supply)
PoE Power Consumption	Each power $\leq 30W$ , Total $\leq 370W$
PoE Protocol	IEEE802.3af, IEEE802.3at
Switching Capacity	24.8G
Packet Forwarding Rate	9.52Mpps
Humidity	10%-90%
Power	AC 100~240V

# FSW24816X



سوئیچ ۲۴ پورت

Combo

16 × SFP

8 × GB

# FSW24816X



Interfaces	1000M SFP port x 16 Combo 1000BASE-T/SFP port x 8
Management Ports	One Console port
Reset Button	One Restore Factory Default Button
Switching Capacity	350Gbps
Packet Forwarding Rate	35.7Mpps
Working Temperature	-10~55°C
Storage Temperature	-40~70°C
Operating Humidity	5%~95% Non-condensing

# FSW2404-24G



سوئیچ ۲۴ پورت

Combo

4 × SFP

24 × GB

# FSW2404-24G



Interfaces	10/100/1000BASE-T port x 20 Combo 1000BASE-T/SFP port x 4
Management Ports	One Console port
Reset Button	One Restore Factory Default Button
Switching Capacity	350Gbps
Packet Forwarding Rate	35.7Mpps
Working Temperature	-10~55°C
Storage Temperature	-40~70°C
Operating Humidity	5%~95% Non-condensing

# FSW0811-8P

## سوئیچ 8 پورت PoE

1 × SFP

1 × GB





# FSW0811-8P

Ethernet Port	1*1000 Base-X 1*10/100/1000 Base-T 8*10/100 Base-T (PoE power supply)
PoE Power Consumption	Each power $\leq 30W$ , Total $\leq 96W$
PoE Protocol	IEEE802.3af, IEEE802.3at
Switching Capacity	7.6G
Packet Forwarding Rate	4.17Mpps
Packet Buffer Memory	1Mb
MAC Table Size	8K
Flow Control	Enable by default
Application Humidity	10%~90%
Power	DC48~57V



با ما تماس بگیرید:



۰۲۱-۶۶۹۴۹۶۶۶